

ZPMV2.E121233 Wiring, Printed- Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed- Component

[See General Information for Wiring, Printed - Component](#)

TECHBOARD SRL
VIA DELLA SCIENZA N 50
41100 MODENA, MO ITALY

E121233

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Solder		Max	Flame Class	Meets	C
	Min	Edge			Area	Limits	Temp	UL796		T	
	mm(in)	mm(in)			Diam mm(in)	C	sec	C		DSR	I
Multilayer printed wiring boards.											
RL-M-94V-0	0.09 (0.004)	0.19 (0.007)	17 (0.67) Int:102	DS	76.2 (3.0)	288	20	130	V-0	All	-
RL-M1-94V-0	0.10 (0.004)	0.10 (0.004)	17 (0.67) Int:102	DS	76.2 (3.0)	288	20	130	V-0	All	-
RL100	0.1 (0.004)	0.1 (0.004)	16.5 (0.65) Int:66	DS	50.8 (2.0)	265	10	120	V-0	All	*
RL102	0.14 (0.006)	0.15 (0.006)	21 (0.83) Int:34.3	DS	12.8 (0.5)	288	10	130	V-0	All	*
RL103	0.15 (0.006)	0.13 (0.005)	16.5 (0.65) Int:36	DS	50.8 (2.0)	288	10	130	V-0	All	3
RL104	0.14 (0.006)	0.15 (0.006)	21 (0.83) Int:34.3	DS	50.8 (2.0)	288	10	130	V-0	All	3
Single layer printed wiring boards.											
RL-D-94V-0	0.09 (0.004)	0.19 (0.007)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	-
RL-D1-94V-0	0.09 (0.004)	0.19 (0.007)	17 (0.67)	DS	25.4 (1.0)	260	20	130	V-0	All	-
RL01	0.1 (0.004)	0.1 (0.004)	16.5 (0.65)	DS	50.8 (2.0)	265	10	120	V-0	All	3
RL02	0.08 (0.003)	0.08 (0.003)	16.5 (0.65)	DS	50.8 (2.0)	260	10	130	V-0	All	*
RL130	0.08 (0.003)	0.08 (0.003)	16.5 (0.65)	DS	50.8 (2.0)	260	10	130	V-0	All	*
RL99	0.1 (0.004)	0.1 (0.004)	16.5 (0.65)	DS	50.8 (2.0)	265	10	120	V-0	All	*

* - CTI PLC is marked on individual board.

DS - Double-Sided

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.



Marking: Company name or trademark  ,  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2011-11-04

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"